

K KEMMLER®

Präzisionswerkzeuge

Shrink chuck 4,5° BT 40 - 20 - 90



117,81 € *

* Prices excl. legal value added tax plus shipping costs

Brand: Kemmler GmbH
Order no.: 406.70.20



Application:

For mounting tools with straight shanks.

Note:

Toolholders suitable for induction-, contact- and hot air shrink units. Ø 3, 4, 5 with h4-tolerance and Ø 6 – Ø 32 with h6-tolerance

For Ø 3, 4 and 5 mm only solid carbide tool shanks must be used!

- All holders are made of forged steel
- Specific, low warpage hardened
- Surface hardened HRC 58~60
- Hardening depth 0,8mm~0,9mm
- Taper angle tolerance < AT 3 according to DIN 2080
- Surface roughness Ra < 0,4 µm
- Tensile strength in the core of min. 800 N/mm² after DIN
- All functional surfaces fine machined

Article properties

ADINTMS:	ISO 7388-2 (MAS-BT)
ADINTWS:	Schrumpffutter 4,5°
ADJRG:	10
Auswuchtgüte:	G2,5 25.000 1/min
BD2:	42
BTED:	33
CNSC:	JD/JF (AD/B)
DCONWS:	20
LPR:	90
LSCN:	41
LSCX:	51
Rundlauf:	< 3µm
SK:	BT 40
TDCON:	h6
THID:	M16x1