

Shell mill holder HSK 100 - 27 - 100



214,20 € \* \* Prices excl. legal value added tax plus shipping costs

Brand: Kemmler GmbH Order no.: A100.11.27.1



Application:

For mounting milling cutters with transversal groove.

## Note:

d = 40/d = 60: For large diameter face mill cutters with four additional threaded holes according to DIN 2079.

SK 30 without coolant exit bores on the end face

## Delivery:

With drivers, cross head retaining screw and cylinder head retaining screw for cutters with central coolant. For d = 60 only with four fi xation screws according to DIN 912.

- All holders are made of forged steel
- Specific, low warpage hardened
- Surface hardened HRC 58~60
- Hardening depth 0,8mm~0,9mm
- Taper angle tolerance < AT 3 according to DIN 2080
- Surface roughness Ra < 0,4 μm
- Tensile strength in the core of min. 800 N/mm<sup>2</sup> after DIN
- All functional surfaces fine machined

## Article properties

TDCON:	h6
ADINTMS:	ISO 12164 (HSK-A)
ADINTWS:	DIN 6357 (Quernut)
Auswuchtgüte:	G2,5   25.000 1/min
BD1:	58
CXSC:	Kühlkanäle
DCONWS:	27
DCP:	Ja
DCPS:	D10/H4,5
HSK:	HSK-A 100
LB:	71
LF:	100

## 17.05.2024

LSC:	21
max. Rundlaufabweichung:	< 5µm