

K KEMMLER®

Präzisionswerkzeuge

Shell mill holder SK 50 - 60 - 55



148,00 € *

* Prices excl. legal value added tax plus shipping costs

Brand: Kemmler GmbH

Order no.: 501.11.60

Application:

For mounting milling cutters with transversal groove.

Note:

d = 40/d = 60: For large diameter face mill cutters with four additional threaded holes according to DIN 2079.

SK 30 without coolant exit bores on the end face

Delivery:

With drivers, cross head retaining screw and cylinder head retaining screw for cutters with central coolant. For d = 60 only with four fixation screws according to DIN 912.

- All holders are made of forged steel
- Specific, low warpage hardened
- Surface hardened HRC 58~60
- Hardening depth 0,8mm~0,9mm
- Taper angle tolerance < AT 3 according to DIN 2080
- Surface roughness Ra < 0,4 µm
- Tensile strength in the core of min. 800 N/mm² after DIN
- All functional surfaces fine machined

Article properties

ADINTMS:	DIN 2080
ADINTWS:	DIN 6357 (Quernut)
Auswuchtgüte:	G6,3 15.000 1/min
BD:	129
CNSC:	AD
DCONWS:	60
LSC:	40
Rundlauf:	< 5µm
SK:	SK 50
TDCON:	h6
LF:	55

