

**Morse taper adaptor SK 50 - 3 - 65****96,00 € \***

\* Prices excl. legal value added tax plus shipping costs

Brand: Kemmler GmbH

Order no.: 502.08.03

**Application:**

For clamping tools with Morse taper shank and thread according to DIN 228-1 form A.

**Delivery:**

With built-in tightening bolt

- All holders are made of forged steel
- Specific, low warpage hardened
- Surface hardened HRC 58~60
- Hardening depth 0,8mm~0,9mm
- Taper angle tolerance < AT 3 according to DIN 2080
- Surface roughness Ra < 0,4 µm
- Tensile strength in the core of min. 800 N/mm² after DIN
- All functional surfaces fine machined

**Article properties**

|               |                        |
|---------------|------------------------|
| ADINTMS:      | ISO 7388-1 (DIN 69871) |
| ADINTWS:      | DIN 6364               |
| Auswuchtgüte: | G6,3   15.000 1/min    |
| BD:           | 40                     |
| CNSC:         | AD                     |
| CTWS:         | 3                      |
| DCP:          | Ja                     |
| DCPS:         | D10/H4,5               |
| LPR:          | 65                     |
| Rundlauf:     | < 5µm                  |
| SK:           | SK 50                  |
| THID:         | M12                    |