KEMMLER®
Präzisionswerkzeuge

Hydraulic expansion chuck BT 50 - 16 - 110

384,00 € *
* Prices excl. legal value added tax plus shipping costs

Brand: Kemmler GmbH
Order no.: 505.H16

Application:
For mounting straight-shank tools acc. DIN 1835 form A+B+E and DIN 6535 form HA+HB+HE (larger than dia. 20 mm only with reduction sleeve).

Note:
l1 = max. clamping depth
l2 = max. length adjustment range

Delivery:
With wrench

- All holders are made of forged steel
- Specific, low warpage hardened
- Surface hardened HRC 58~60
- Hardening depth 0,8mm~0,9mm
- Taper angle tolerance < AT 3 according to DIN 2080
- Surface roughness Ra < 0,4 µm
- Tensile strength in the core of min. 800 N/mm² after DIN
- All functional surfaces fine machined

Article properties

ADINTMS:	ISO 7388-2 (MAS-BT)
ADINTWS:	Hydro-Dehnspannfutter
ADJRGA:	10
Auswuchtgüte:	G2,5 | 25.000 1/min
BD:	38
BD2:	80
CNSC:	JD/JF (AD/B)
DCONWS:	16
DRVS:	5
LBD1:	45
LPR:	110
LSCX:	52
Rundlauf:	< 3µm
SK:	BT 50
THID:	M12x1