

Shell mill holder BT 50 - 27 - 100



102,00 € * * Prices excl. legal value added tax plus shipping costs

Brand: Kemmler GmbH Order no.: 506.11.27.1



Application:

For mounting milling cutters with transversal groove.

Note:

d = 40/d = 60: For large diameter face mill cutters with four additional threaded holes according to DIN 2079.

SK 30 without coolant exit bores on the end face

Delivery:

With drivers, cross head retaining screw and cylinder head retaining screw for cutters with central coolant. For d = 60 only with four fi xation screws according to DIN 912.

- All holders are made of forged steel
- Specific, low warpage hardened
- Surface hardened HRC 58~60
- Hardening depth 0,8mm~0,9mm
- Taper angle tolerance < AT 3 according to DIN 2080
- Surface roughness Ra < 0,4 μm
- Tensile strength in the core of min. 800 N/mm² after DIN
- All functional surfaces fine machined

Article properties

ADINTMS:	ISO 7388-2 (MAS-BT)
ADINTWS:	DIN 6357 (Quernut)
Auswuchtgüte:	G2,5 25.000 1/min
BD:	58
CNSC:	JD/JF (AD/B)
CXSC:	Kühlkanäle
DCONWS:	27
LB2:	62
LF:	100
LSC:	21
Rundlauf:	< 5µm
SK:	BT 50

25.04.2024

TDCON: h6