
KEMMLER®
Präzisionswerkzeuge

Shrink chuck 4,5° BT 50 - 12 - 120





230,00 € *
* Prices excl. legal value added tax plus shipping costs

Brand: Kemmler GmbH
Order no.: 506.71.12.1

Application:
For mounting tools with straight shanks.

Note:
Toolholders suitable for induction-, contact- and hot air shrink units. Ø 3, 4, 5 with h4-tolerance and Ø 6 – Ø 32 with h6-tolerance

---

For Ø 3, 4 and 5 mm only solid carbide tool shanks must be used!

- All holders are made of forged steel
- Specific, low warpage hardened
- Surface hardened HRC 58~60
- Hardening depth 0,8mm~0,9mm
- Taper angle tolerance < AT 3 according to DIN 2080
- Surface roughness Ra < 0,4 µm
- Tensile strength in the core of min. 800 N/mm² after DIN
- All functional surfaces fine machined

Article properties

ADINTMS:	ISO 7388-2 (MAS-BT)
ADINTWS:	Schrumpffutter 4,5°
ADJRGA:	10
Auswuchtgüte:	G2,5 | 25.000 1/min
BD2:	32
BTED:	24
CNSC:	JD/JF (AD/B)
DCONWS:	12
LPR:	120
LSCN:	36
LSCX:	46
Rundlauf:	< 3µm
SK:	BT 50
TDCON:	h6
THID:	M10x1