KEMMLER®
Präzisionswerkzeuge

# End mill holder Whistle-Notch HSK 100 - 40 - 120





**194,00 € ***
* Prices excl. legal value added tax plus shipping costs

Brand: Kemmler GmbH
Order no.: A100.05.40

**Application:**
For mounting straight-shank tools and inclined flat according to DIN 1835 form E (Whistle Notch).

**Delivery:**
With clamping screw and axial adjustment bolt

- All holders are made of forged steel
- Specific, low warpage hardened
- Surface hardened HRC 58~60
- Hardening depth 0,8mm~0,9mm
- Taper angle tolerance < AT 3 according to DIN 2080
- Surface roughness Ra < 0,4 µm
- Tensile strength in the core of min. 800 N/mm² after DIN
- All functional surfaces fine machined

**Article properties**

| | |
|---|---|
| ADINTMS: | ISO 12164 (HSK-A) |
| ADINTWS: | DIN 6359 (Whistle Notch) |
| Auswuchtgüte: | G2,5 \| 25.000 1/min |
| BD: | 80 |
| DCONWS: | 40 |
| DCP: | Ja |
| DCPS: | D10/H4,5 |
| HSK: | HSK-A 100 |
| LPR: | 120 |
| max. Rundlaufabweichung: | < 3µm |