KEMMLER®
Präzisionswerkzeuge

## Combi shell mill holder HSK 63 - 16 - 60





**117,00 € ***
* Prices excl. legal value added tax plus shipping costs

Brand: Kemmler GmbH
Order no.: A63.10.16

**Application:**
For mounting milling cutters with transverse or longitudinal groove.

---

**Delivery:**
With retaining screw, driving ring and feather key

---

- All holders are made of forged steel
- Specific, low warpage hardened
- Surface hardened HRC 58~60
- Hardening depth 0,8mm~0,9mm
- Surface roughness Ra < 0,4 µm
- Tensile strength in the core of min. 800 N/mm² after DIN
- All functional surfaces fine machined

**Article properties**

| | |
|---|---|
| TDCON: | h6 |
| ADINTMS: | ISO 12164 (HSK-A) |
| ADINTWS: | DIN 6358 (Kombi) |
| Auswuchtgüte: | G6,3 \| 15.000 1/min |
| BD: | 32 |
| DCONWS: | 16 |
| DCP: | Ja |
| DCPS: | D10/H4,5 |
| HSK: | HSK-A 63 |
| LF1: | 60 |
| LF2: | 50 |
| LSCN: | 17 |
| LSCX: | 27 |
| max. Rundlaufabweichung: | < 5µm |