

K KEMMLER®

Präzisionswerkzeuge

Shrink chuck 4,5° PSK 40 - 06 - 75

**324,00 € ***

* Prices excl. legal value added tax plus shipping costs

Brand: Kemmler GmbH

Order no.: C4.70.06

Application:

For mounting tools with straight shanks.

Note:

Toolholders suitable for induction-, contact- and hot air shrink units. Ø 6 – Ø 32 with h6-tolerance

For Ø 3, 4 and 5 mm only solid carbide tool shanks must be used!

Delivery:

- All holders are made of forged steel
- Specific, low warpage hardened
- Surface hardened HRC 58~60
- Hardening depth 0,8mm~0,9mm
- Taper angle tolerance < AT 3 according to DIN 2080
- Surface roughness Ra < 0,4 µm
- Tensile strength in the core of min. 800 N/mm² after DIN
- All functional surfaces fine machined

Article properties

ADINTMS:	CCS - Polygonschaftkegel
ADINTWS:	Schrumpffutter 4,5°
ADJRG:	10
Auswuchtgüte:	G2,5 25.000 1/min
BD:	27
BTED:	21
DCONWS:	6
LPR:	75
LSCN:	26
LSCX:	36
PSK:	C4 PSK 40
Rundlauf:	< 3µm
TDCON:	h6
THID:	M8x1