14.05.2024



EMMLER

Präzisionswerkzeuge

Shell mill holder PSK 63 - 32 - 40



239,00 € *

* Prices excl. legal value added tax plus shipping costs

Brand: Kemmler GmbH Order no.: C6.11.32



Application

For mounting milling cutters with transversal groove.

Note:

d = 40/d = 60: For large diameter face mill cutters with four additional threaded holes according to DIN 2079.

Delivery:

With drivers, cross head retaining screw and cylinder head retaining screw for cutters with central coolant. For d = 60 only with four fi xation screws according to DIN 912.

- All holders are made of forged steel
- Specific, low warpage hardened
- Surface hardened HRC 58~60
- Hardening depth 0,8mm~0,9mm
- Taper angle tolerance < AT 3 according to DIN 2080
- Surface roughness Ra < 0,4 μ m
- Tensile strength in the core of min. 800 $\ensuremath{\text{N}/\text{mm}^2}$ after DIN
- All functional surfaces fine machined

Article properties

ADINTMS: CCS - Polygonschaftkegel
ADINTWS: DIN 6357 (Quernut)
Auswuchtgüte: G2,5 | 25.000 1/min

BD: 78

CXSC: Kühlkanäle

DCONWS: 32
DCP: Ja
DCPS: D10/H4,5
LB: 18
LF: 40
LSC: 24

PSK: C6 | PSK 63
Rundlauf: < 5μm
TDCON: h6