




## Shell mill holder BT 40 - 40 - 50



**138,00 € \***

\* Prices excl. legal value added tax plus shipping costs

Brand: Kemmler GmbH  
Order no.: DC.406.11.40



### Application:

For mounting milling cutters with transversal groove.

### Note:

d = 40/d = 60: For large diameter face mill cutters with four additional threaded holes according to DIN 2079.

SK 30 without coolant exit bores on the end face

### Delivery:

With drivers, cross head retaining screw and cylinder head retaining screw for cutters with central coolant. For d = 60 only with four fixation screws according to DIN 912.

- All holders are made of forged steel
- Specific, low warpage hardened
- Surface hardened HRC 58~60
- Hardening depth 0,8mm~0,9mm
- Taper angle tolerance < AT 3 according to DIN 2080
- Surface roughness Ra < 0,4 µm
- Tensile strength in the core of min. 800 N/mm² after DIN
- All functional surfaces fine machined

### Article properties

ADINTMS:	DUAL CONTACT ~ISO 7388-2
ADINTWS:	DIN 6357 (Quernut)
Auswuchtgüte:	G2,5   25.000 1/min
BD:	88
CNSC:	JD/JF (AD/B)
CXSC:	Kühlkanäle
DCONWS:	40
LB2:	23
LF:	50
LSC:	27

---

Rundlauf:	< 5µm
TDCON:	h6