

# K KEMMLER®

## Präzisionswerkzeuge

### Morse taper adaptor SK 40 - 2 - 50

**75,00 € \***

\* Prices excl. legal value added tax plus shipping costs

Brand: Kemmler GmbH  
Order no.: DC.403.07.02**Application:**

For mounting tools with Morse taper shank and tang according to DIN 228-1 form B.

- All holders are made of forged steel
- Specific, low warpage hardened
- Surface hardened HRC 58~60
- Hardening depth 0,8mm~0,9mm
- Taper angle tolerance < AT 3 according to DIN 2080
- Surface roughness Ra < 0,4 µm
- Tensile strength in the core of min. 800 N/mm² after DIN
- All functional surfaces fine machined

**Article properties**

|               |                          |
|---------------|--------------------------|
| ADINTMS:      | DUAL CONTACT ~ISO 7388-1 |
| ADINTWS:      | DIN 6383                 |
| Auswuchtgüte: | G6,3   15.000 1/min      |
| BD:           | 32                       |
| CNSC:         | AD/AF (AD/B)             |
| CTWS:         | 2                        |
| DCP:          | Ja                       |
| DCPS:         | D10/H4,5                 |
| LB:           | 19                       |
| LPR:          | 50                       |
| Rundlauf:     | < 5µm                    |
| SK:           | SK-DC 40                 |
| TDCON:        | AT5                      |