

# K KEMMLER®

## Präzisionswerkzeuge

### Shell mill holder SK 40 - 40 - 130

**126,00 € \***

\* Prices excl. legal value added tax plus shipping costs

Brand: Kemmler GmbH

Order no.: 403.11.40.130

**Application:**

For mounting milling cutters with transversal groove.

**Note:**

d = 40/d = 60: For large diameter face mill cutters with four additional threaded holes according to DIN 2079.

SK 30 without coolant exit bores on the end face

**Delivery:**

With drivers, cross head retaining screw and cylinder head retaining screw for cutters with central coolant. For d = 60 only with four fixation screws according to DIN 912.

- All holders are made of forged steel
- Specific, low warpage hardened
- Surface hardened HRC 58~60
- Hardening depth 0,8mm~0,9mm
- Taper angle tolerance < AT 3 according to DIN 2080
- Surface roughness Ra < 0,4 µm
- Tensile strength in the core of min. 800 N/mm² after DIN
- All functional surfaces fine machined

**Article properties**

ADINTMS:	ISO 7388-1 (DIN 69871)
ADINTWS:	DIN 6357 (Quernut)
Auswuchtgüte:	G2,5   25.000 1/min
BD:	88
CNSC:	AD/AF (AD/B)
CXSC:	Kühlkanäle
DCONWS:	40
DCP:	Ja
DCPS:	D10/H4,5
LB2:	110,9

---

LF:	130
LSC:	27
Rundlauf:	< 5µm
SK:	SK 40
TDCON:	h6