

**ER-Precision collet with cooling channels ER32 | 470ECP | < 3 µm | Ø 5,0****54,00 € ***

* Prices excl. legal value added tax plus shipping costs

Brand: Kemmler GmbH
Order no.: 470ECP-05**Application:**

For mounting straight-shank tools in collet chucks ISO 15488 (ex. DIN 6499).

Version:

Metallic sealed collets with cooling channels. Applicable up to 100 bar.

System concentricity and repetition accuracy 3 µm (3×D, maximum = 50 mm), in conjunction with „KEMMLER Precision collet chuck ER“.

Suitable for:

KEMMLER Precision collet chuck ER or standard collet chuck Spannfutter ISO 15488 (ex. DIN 6499).

Note:

Only nominal size d can be clamped, with cooling channels. In order to achieve an optimum sealing the tool must be clamped on the complete length of the ground drill of the collet. Applicable up to 100 bar.

Article properties

Typ:	470E ER 32
SEAL:	Ja
ADINTMS:	ER collet ISO10897 (DIN6388) - ER32
ADINTWS:	Cylindrical clamping - metric
BD:	33
CP:	21 bar
CXSC:	Kühlkanäle
DCONWS:	5
OAL:	40
Rundlaufgenauigkeit:	< 3µm