

**Shrink chuck 4,5° PSK 63 - 10 - 120****350,00 € \***

\* Prices excl. legal value added tax plus shipping costs

Brand: Kemmler GmbH

Order no.: C6.70.10.1



PSK = PSK 63

d = 10

A = 120

D = 24

max. clamping depth = 41

**Application:**

For mounting straight-shank tools.

**Note:**

Toolholders suitable for induction-, contact- and hot air shrink units. Ø 3, 4, 5 with h4-tolerance and Ø 6 - Ø 32 with h6-tolerance  
For Ø 3, 4 and 5 mm only solid carbide tool shanks must be used!

**Article properties**

|               |                          |
|---------------|--------------------------|
| ADINTMS:      | CCS - Polygonschaftkegel |
| ADINTWS:      | Schrumpffutter 4,5°      |
| ADJRG:        | 10                       |
| Auswuchtgüte: | G2,5   25.000 1/min      |
| BD:           | 32                       |
| BTED:         | 24                       |
| DCONWS:       | 10                       |
| LPR:          | 120                      |
| LSCN:         | 31                       |
| LSCX:         | 41                       |
| PSK:          | C6   PSK 63              |
| Rundlauf:     | < 3µm                    |
| TDCON:        | h6                       |
| THID:         | M10x1                    |